

Revised
January 2002



9411 Corsair Road
Frankfort, IL 60423
1-800-552-0299 Phone
1-815-464-5650 Fax

EMERGENCY PHONE 1-800-255-3924

MATERIAL SAFETY DATA SHEETS

TORQUE 177

HMIS;	HEALTH	2	FLAMMABILITY	1	REACTIVITY	1
NFPA	HEALTH	2	FIRE HAZARD	1	REACTIVITY	1

1. GENERAL INFORMATION

PRODUCT NAME:
TECHINICAL NAME:

Torque 177
Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	CAS No.	%
Aromatic dimethacrylate	24448-20-2	10-20
Urethane methacrylate resin	5888-33-5	50-60
Hydroxyalkyl methacrylate	27813-02-1	5-15
Acrylic acid*	79-10-7	1-5
Organic peroxide*	80-15-9	1-2
Amorphous silica	112945-52-5	1-5
PTFE	9002-84-0	2-10

* This component is listed as a SARA Section 313 Toxic Chemical.

Ingredients which have exposure limits

Exposure Limits (TWA) Ingredients	ACGIH (TLV)	OSHA (PEL)	OTHER
Organic peroxide	None	None	1ppm(6mg/m3) Skin(WHEEL)
Hydroxyalkyl methacrylate	None	None	1 ppm TWA 3 ppm STEL
Acrylic acid	2 ppm TWA skin 5.9 mg/m3 skin	10 ppm TWA skin 30 mg/m3 skin	1 ppm TWA skin 3 ppm STEL skin

3. HAZARD IDENTIFICATION

Toxicity:

Liquid and Vapors are an eye and skin irritant.

Primary Routes of Entry:

None known

Signs and Symptoms of Exposure:

May cause dermatitis on prolonged contact in sensitive individuals.

Existing Conditions Aggravated by Exposure:

Acrylic acid: Upper respiratory and lung diseases, dermatitis

4. FIRST AID MEASURES

Ingestion:

Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation:

Does not apply

Skin Contact:

Wash with soap and water.

Eye Contact:

Flush at least 15 minutes with plenty of water. Obtain medical attention.

5. FIREFIGHTING MEASURES

Flash Point:

More than 200°F

Extinguishing Agents:

Carbon dioxide, foam, dry chemical

Special Firefighting

Procedures:

Not available

Hazardous Products formed

by Fire or Thermal Decomposition Irritating organic vapors

Unusual Fire or Explosion Hazards:

None



MATERIAL SAFETY DATA SHEETS

TORQUE 177



6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case of spill or leak:

Soak up with an inert absorbent. Store in closed container until disposal.

7. HANDLING AND STORAGE

Safe Storage:
Handling:

Store at or below 100°F
Avoid prolonged contact with eyes and skin.

8. EXPOSURE AND PERSONAL PROTECTION

Eyes:
Skin:
Ventilation:
Respiratory

Safety glasses or goggles.
Neoprene, rubber, or butyl rubber gloves.
Sufficient to maintain vapors concentration below TLV.
Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:
Odor:
Boiling Point:
pH:
Solubility in Water:
Specific Gravity
Vapor Pressure:
Vapor Density:
Evaporation Rate
(Ether = 1)

White liquid
Sharp, irritating
More than 300°F
Does not apply
Slight
1.1 at 25°C
Less than 0,5 mmbar at 20°C
Not available
Not available

10. REACTIVITY

Stability:
Hazardous Polymerization:
Incompatibility:
Conditions to Avoid:
Hazardous Decomposition
Products (non-thermal):

Stable
Will not occur
None
Not available
None

11. TOXICOLOGICAL INFORMATION

Estimated oral LD50 more than 5000 mg/kg.
Estimated dermal LD50 more than 2000 mg/kg.

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal:
EPA Hazardous Waste Number

Incinerate following EPA and local regulations.
NH - Not a RCRA Hazardous Waste Material



MATERIAL SAFETY DATA SHEETS

TORQUE 177



14. TRANSPORTATION INFORMATION

DOT (49 CFR 172)
Domestic Ground Transport
Proper Shipping Name:
Hazard Class or Division:
Identification Number:
Marine Pollutant:
IATA
Proper Shipping Name:
Class or Division:
UN or ID Number:

Unrestricted
Unrestricted
None
None
Unrestricted
Unrestricted
None

Engineering Excellence

For technical information
and support call **1-800-552-0299** or visit our website at

www.instantca.com