



SOUND BLOK PLUS

Weight	7.25 lbs/roll
Color	Black
Dimension	47-1/4" W x 25'-7/16" L
Roll dimension	47-1/4" X 7.5" diameter
Density, pcf	20 lbs.
Thickness (+/-5% manufacturing tolerance)	3mm/.10"
Square yards/Roll	11.11
Anti-Microbial	Yes
Shipping Weight	7.25 lbs/roll
COC FF 1-70 (Pill Test)	Pass
Liner	EVA w/PE Water Barrier
Moisture Vapor Transmission Rate	1.3g/m ² /24hrs
Maximum subfloor moisture emission rate	5 lbs/1000sf/24 hrs (calcium chloride test)
Thermal "R" Factor	.10
Impact Insulation Class (rating for floating floor installation)	IIC-72 (Under Floating Laminate Floor) (ASTM E492)
Sound Transmission Class (rating for floating floor installation)	STC-73 (under Floating Laminate Floor) (ASTM E90)

Product Installation

- Sound Blok Plus acoustic floor underlay is versatile and is designed for glued or floating floor installation.
**Always follow wood flooring manufacturer installation instructions.*
- Sound Blok Plus acoustic underlayment must be installed on a clean, dry, level surface (i.e., a standard wood subfloor or concrete slab).
- Roll out Sound Blok Plus acoustic underlayment across the floor so that the mat rests against the outer layer of the wall.
- Make sure there are no attachments or penetrations through the Sound Blok Plus acoustic underlayment.
- Install the underlay with Vapor banner side to the subfloor.
- Install finished floor.
- Trim away excess underlayment and install baseboard or other trim.