

# Portable Zero Air Source Model 2020



## Overview

The Model 2020 is a portable source for clean, dry air designed to meet a wide range of requirements for the environmental industry. From supplying air for calibration systems to purge air for permeation ovens, the small package size and weight make the Model 2020 the preferred choice for field and audit personnel as well as operating environments with limited bench space.

The Model 2020 uses an internal permeation drying system for moisture removal and is coupled with filter canisters for scrubbing NO, NO<sub>2</sub>, O<sub>3</sub>, SO<sub>2</sub> and H<sub>2</sub>S. Optional features such as the internal carbon monoxide (CO) oxidizer or external hydrocarbon (HC) oxidizer further the Model 2020's clean air capabilities.

## User Benefits

Simple straight-forward controls allow local operation from the front panel, with the option to set the purge frequency and duration for optimum performance. Additionally, the unit automatically drains moisture and pressurized air once powered down.

Remote activation is achieved using the air source control port and cable in conjunction with any Sabio calibrator. This exclusive feature allows the user to start and stop the unit as needed to avoid unnecessary run times; increasing pump life and decreasing service intervals.

## Standard Features

- ▶ Standard 10 LPM @ 20 PSIG
- ▶ Condensate/purge valving for moisture removal
- ▶ Automatic purge frequencies
- ▶ Front panel mounted pressure gauge
- ▶ Front panel mounted adjustable pressure regulator
- ▶ Front panel mounted purge switch
- ▶ Internal permeation dryer
- ▶ Media canisters for removal of NO, NO<sub>2</sub>, O<sub>3</sub>, SO<sub>2</sub>, H<sub>2</sub>S
- ▶ Side mounted carrying strap



## Optional Features

- ▶ Tilt-up front handle with tilt-up front feet
- ▶ High-impact transport case
- ▶ Model 2050 HC Catalytic Oxidizer (separate portable chassis)
- ▶ Dew Point Indicator

## SPECIFICATIONS

*Specifications subject to change without notice*

AIR QUALITY	
Standard unit	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S <0.5 ppb
Standard unit with CO catalytic Oxidizer:	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S <0.5 ppb, CO < 5 ppb
Standard unit with external HC catalytic oxidizer	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S <0.5 ppb, Hydrocarbon ≤ .20 ppb
MECHANICAL	
Height	6.5 in. (16.5 cm)
Width	13.9 in. (35.3 cm)
Depth	15.0 in. (38.1 cm)
Average Weight	23 lbs (10.4 kg)
ELECTRICAL	
Standard	98-132 VAC
Optional	196-264 VAC, 50/60 Hz



Sutron Corporation  
22400 Davis Drive  
Sterling, VA 20164  
703.406.2800  
www.sutron.com  
sales@sutron.com

Air Quality Division  
2111 Sam Bass Road  
Round Rock, TX 78681  
512.238.9359  
www.sutron.com/aq.htm  
salesaqd@sutron.com

Air Quality Division  
2548 Shell Road  
Georgetown, TX 78628  
512.869.0544  
www.sutron.com/aq.htm  
salesaqd@sutron.com

October 13, 2015