

# Zero Air Source Model 1001



## Overview

The Model 1001 Zero Air Source is designed to meet the requirements of clean, dry air for dilution calibrators, purge air for permeation tube ovens, supply air for test chambers and pollutant free air for other laboratory or environmental applications.

Equipped with dual coalescent filters and a permeation drier, moisture removal is enabled automatically using adjustable control circuitry or manual purging from the front panel. Additionally, upon completion of calibration, the air source can be controlled automatically by a Sabio dilution calibrator or remotely by contact closure or when installed on demand with an internal pressure switch.

Air pollutants are removed using reusable dual rear mounted scrubber canisters for NO, NO<sub>2</sub>, O<sub>3</sub>, SO<sub>2</sub>, H<sub>2</sub>S. Other pollutants such as carbon monoxide (CO) or hydrocarbons (HC) can be removed with an internal oxidizer. Both types of internal oxidizers come equipped with front panel mounted temperature controllers which monitor and control the temperature for optimum performance.



## Standard Features

- ▶ Standard 22 SLPM at 25 psig air delivery
- ▶ 3.4 liter surge/condensate tank
- ▶ Condensate/purge valve that operates both automatically and manually to drain condensate
- ▶ Front panel mounted pressure gauge
- ▶ Front panel mounted adjustable pressure regulator
- ▶ Front panel mounted purge switch
- ▶ Automatic control via contact control or a switched low voltage DC power source
- ▶ Internal moisture removal system
- ▶ Media canisters for removal of NO, NO<sub>2</sub>, SO<sub>2</sub>, H<sub>2</sub>S & O<sub>3</sub>
- ▶ Long-life brushless, oil-free compressor
- ▶ Quiet operation

## Optional

- ▶ Internal or external CO catalytic oxidizer
- ▶ Internal HC catalytic oxidizer
- ▶ Internal pressure switch for on-demand pump control
- ▶ Output flow meter
- ▶ Rack-mount kit
- ▶ Dew Point Indicator with LED Indicators
- ▶ Trace Level Scrubbers

## Smaller, Portable Zero Air Source Units Available

- ▶ Model #1001P - High Output
- ▶ Model #2020 - Low Output

<b>Specifications</b> <i>Specifications subject to change without notice</i>		
<b>Air Quality</b>	<b>Standard Unit</b>	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S, < 0.1 ppb
	<b>Standard unit with CO catalytic Oxidizer</b>	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S, < 0.1 ppb, CO < 0.025 ppm
	<b>Standard unit with HC catalytic oxidizer</b>	NO, NO <sub>2</sub> , O <sub>3</sub> , SO <sub>2</sub> , H <sub>2</sub> S, < 0.1 ppb, CO < 5 ppb, & HC < 0.20 ppb
<b>Mechanical</b>	<b>Model 1001 Rack Mount Unit</b>	H: 8.75 in. (22.2 cm) W: 16.2 in. (41.2 cm) D: 22.25 in. (56.5cm)
		Average Weight: 55-65 lbs. (25-30 kg)
	<b>Model 1001P High Output Portable Unit</b>	H: 14.24 in. (36.2 cm) W: 21.0 in. (53.3 cm) D: 24.75in. (62.9 cm)
		Average Weight: 51-61 lbs. (23.1-27.7 kg) Portable Unit
<b>Electrical</b>	<b>Standard</b>	120 VAC 60 Hz, 470 VA operation
	<b>Optional</b>	240 VAC, 50 Hz, 340 VA operation



Sutron Corporation  
22400 Davis Drive  
Sterling, VA 20164  
703.406.2800  
www.sutron.com  
sales@sutron.com

Air Quality Division  
2111 Sam Bass Road  
Round Rock, TX 78681  
512.238.9359  
www.sutron.com/aaq.htm  
salesaqd@sutron.com

Air Quality Division  
2548 Shell Road  
Georgetown, TX 78628  
512.869.0544  
www.sutron.com/aaq.htm  
salesaqd@sutron.com

October 13, 2015