



Company	Hybrid	Technology	Maturity	Row Length (FT)	Row Width (inches)	Number of Rows	Pounds of Grain	% Moisture	Adjusted Test Weight (#)	Corrected Yield (bu/A)
---------	--------	------------	----------	-----------------	--------------------	----------------	-----------------	------------	--------------------------	------------------------

MUNSON	7322VT3P	VT3P	113	656	30	12	5380	26.1	62.5	184.9
MUNSON	M750VT3P	VT3P	115	656	30	6	2632	24.7	61.3	184.3
MUNSON	28020	-	114	656	30	12	4956	26.8	61.8	168.7
MUNSON	6921	-	109	656	30	12	4370	20.4	59.0	161.8
MUNSON	7293	-	112	656	30	12	4426	23.5	62.0	157.4
MUNSON	M660-3000GT	3000GT	106	656	30	12	4136	20.3	60.0	153.3
MUNSON	7423	-	114	656	30	12	4438	25.9	60.5	152.9
MUNSON	2900	-	115	656	30	12	4432	27.8	61.0	148.8
MUNSON	M722GTCBLL	GTCBLL	112	656	30	12	4010	21.2	59.3	146.9

[illegible]

Test Weight Adjustment: Based off of University of Wisconsin Extension publication "Understanding Test Weight", October, 2009. Add 1/4 pound of test weight for each point of moisture beginning at 16% = +1 pound. Example: 54# test weight @ 20% moisture = 54 + 2 = 56#. 18=+1.5; 20=2.0; 22=2.5; 24=3.0; 26=3.5; 28=4.0 etc.

I grant Munson Hybrids, Inc. permission to use my name and information obtained from me to evaluate and market its products.

Signature: _____ Date: _____