



## Small Panel / Down light - Round



MODEL NUMBER:	ENG 006-R		ENG 012-R		ENG 018-R	
WATTS	6W		12W		18W	
UNIT SIZE:	∅120mm		∅170mm		∅225mm	
CUTTING SIZE:	∅100mm		∅150mm		∅200mm	
VOLTAGE	AC: 90-265V		AC: 90-265V		AC: 90-265V	
FREQUENCY	50/60 Hz		50/60 Hz		50/60 Hz	
LUMINOUS FLUX	380LM		860LM		1250LM	
LED CHIP	EPISTAR SMD 2835		EPISTAR SMD 2835		EPISTAR SMD 2835	
CRI	>75		>75		>75	
PF	>0.80		>0.80		>0.80	
DRIVER	Non Dimmable		Non Dimmable		Non Dimmable	
BEAM ANGLE	120		120		120	
BODY MATERIAL	ALUMINIUM (PKW)		ALUMINIUM (PKW)		ALUMINIUM (PKW)	
IP RATING	IP20		IP20		IP20	
CERTIFICATIONS	CE, FCC, ROHS		CE, FCC, ROHS		CE, FCC, ROHS	
COLOUR / SKU	Colour	SKU	Colour	SKU	Colour	SKU
	6000K	770	6000K	776	6000K	782
	4500K	771	4500K	777	4500K	783
	3000K	772	3000K	778	3000K	784

ENG LED Ltd., 7 Beddall Way, Telford TF1 5FN  
 Tel.: 01952 426 070 email: info@engled.co.uk





## Small Panel / Down light – Square



MODEL NUMBER:	ENG 006-SQ		ENG 012-SQ		ENG 018-SQ	
WATTS	6W		12W		18W	
UNIT SIZE:	∅120mm x 120mm		∅170mm x 170mm		∅225mm x 225mm	
CUTTING SIZE:	∅100mm x 100mm		∅150mm x 150mm		∅200mm x 200mm	
VOLTAGE	AC: 90-265V		AC: 90-265V		AC: 90-265V	
FREQUENCY	50/60 Hz		50/60 Hz		50/60 Hz	
LUMINOUS FLUX	380LM		860LM		1250LM	
LED CHIP	EPISTAR SMD 2835		EPISTAR SMD 2835		EPISTAR SMD 2835	
CRI	>75		>75		>75	
PF	>0.80		>0.80		>0.80	
DRIVER	Non Dimmable		Non Dimmable		Non Dimmable	
BEAM ANGLE	120		120		120	
BODY MATERIAL	ALUMINIUM (PKW)		ALUMINIUM (PKW)		ALUMINIUM (PKW)	
IP RATING	IP20		IP20		IP20	
CERTIFICATIONS	CE, FCC, ROHS		CE, FCC, ROHS		CE, FCC, ROHS	
COLOUR / SKU	Colour	SKU	Colour	SKU	Colour	SKU
	6000K	773	6000K	779	6000K	785
	4500K	774	4500K	780	4500K	786
	3000K	775	3000K	781	3000K	787

ENG LED Ltd., 7 Beddall Way, Telford TF1 5FN  
Tel.: 01952 426 070 email: info@engled.co.uk

