




TIG 200DC PULSE PFC



Global Voltage $\frac{CC}{DC}$ **1** Phase



**WIDE
VOLTAGE**



POWER GENERATOR
1~110V 5KW/6.5KVA
1~230V 7KW/8.5KVA

- Friendly Digital Control Panel makes easily welding parameters setting
- Digital Display can show parameters setting exactly
- Wireless Remote Control is optional, remote control distance can be up to 100m
- 3 In 1 Multi functions includes HF TIG/MMA/LIFT TIG
- Pulse Function makes excellent welding performance, special for thin material welding
- Pre Flow Time is adjustable from 0 to 2 seconds
- Post Flow time is adjustable from 0 to 10 seconds
- Built-in Protection Circuit of over temperature and over voltage and over current for better reliability
- Protections including overheat, overvoltage, low voltage and overcurrent
- *90-270 Volts Input can be worked in Global market
- PFC Technology makes power factor more than 0.99 and energy saving.

MODEL	TIG 200DC PULSE PFC			
Rated Input Voltage(V)	90VAC270VAC			
Frequency(HZ)	50/60			
Input Voltage(V)	1110/115±10%		1220/230/240±10%	
Current Range(A)	10100		10200	
Function	TIG	MMA	TIG	MMA
Duty Cycle(40℃ 10min)	90% 120A	60% 120A	50% 200A	35% 200A
	100% 105A	100% 95A	100% 160A	100% 135A
Rated Input Power(KW)	2.7	3.6	4.4	7
Rated Input Current(A)	24.5	33	20	32
No Load Voltage(V)	66			
Welding Current Range(A)	5120		5200	
UP slope/Down slope Flow(S)	05			
Pre/Post Flow(S)	02/010			
Pulse frequency(HZ)	0.5200			
Pulse width range(%)	0100			
Efficiency(%)	≥85			
Power Factor	0.99			
N.W.(KG)	9			
Protection Class	IP23			
Insulation Class	H			
Dimensions(MM)	450*135*250			
Electrode Diameter	Φ1.6 Φ4.0			
Cooling	AF			

Optional Accessories:

