

# QUICK-SLING

## The safe & affordable install

*Applicable for residential or light commercial installations*



Quick-Sling SPECS  
QSLG1000

### A Close Up:



Each arm attaches to wood using 2 zip screws for stability & a 4" through bolt & wing nut for security. Installs to steel using steel beam adapters.



28 points of anti-vibration isolation is provided using four 50-derometer self-adhesive rubber pads & 24 rubber washers.



Extension arms individually adjust in one inch increments using thumb screws & wing nuts for speed & versatility. Installs as high as 24" or as low as 48" on flat or pitched roofs.



32" secondary drain pan hangers are provided & install in seconds.  
\*Drain pan not included.



Our Quick-Sling is made of 14-gauge square, steel tubing which not only cuts down on vibration but is also able to hold up to 400 lbs.



3 Dimensionally Adjustable  
Height: 24" to 48"  
Width: 38" to 48"  
Length: 32" to 48"

\*Powder Coated.

Quick-Sling provides you with a non-swinging, solid platform that is quick, safe, stable and affordable.

U.S. Patent No. 8,701,261

Quick-Sling 391 West Water Street Taunton, MA 02780

P:1.800.699.0453 F:1.800.699.0423

[www.Quick-Sling.com](http://www.Quick-Sling.com)

\*Quick-Sling offers a 2-year warranty on steel, workmanship; 1-year warranty on powder coating.