

32Amp 230V

Model Name  
**ATS**

Model Number  
**ATS-3223C-10N2**



- Meter** True RMS Current Meter.
- Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software
- Protocols** Http, Https, SNMP, DHCP, UDP, SSL(verified by IE8 on WinXP)
- Installed in Rack** Horizontal
- Power Action** Automatic Transfer Switch
- Event Alert** Email, Trap
- Option Device** Temp./Humidity Probe
- Protection** Circuit Breaker

### General

Output	(10) IEC320 C13
Input	(2) attached IEC309 32A 2P+E plugs,3 meters
Output Protection	(2) 16 AMP Circuit Breaker

### Communication

SSL Indication	(1) Yellow LED
DHCP Indication	(1) Green LED
Output Status	(2) Green LED
Input Status	(2) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(1) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

### Power Information

Voltage	+/- 2% @ 90V~260V
Active Power	+/- 2% @ 50W~5000W
Apparent Power	+/- 2% @ 50VA~5000VA
Frequency	+/- 2% @ 45~65Hz
Power Factor	+/- 0.02 @ 0.5~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/-2% @ 50W~5000W, kh=1.0
Current	Range: 0A ~ 32 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP

### Operation

Nominal Voltage	200V ~240V
On-Line Voltage	180V~ 262V
Frequency	50/60Hz
Max. Output Current	32 Amp
Transfer Time	8~16ms
Operation Temp.	0 ~ 40 Celsius degree
Humidity	0% ~ 90%
Size	260 x 432 x 44.45 mm
Net Weight	7 kg

