

32Amp 230V

Model Name  
**ATS**

Model Number  
**ATS-3223T-01T1**



**Meter** True RMS Current Meter.

**Power Monitor** Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

**Protocols** Http, Https, SNMP, DHCP, UDP, SSL(verified by IE8 on WinXP)

**Installed in Rack** Horizontal

**Power Action** Automatic Transfer Switch

**Event Alert** Email, Trap

**Option Device** Temp./Humidity Probe

### General

Output (1) Terminal Block  
Input (2) Terminal Block

### Communication

SSL Indication (1) Yellow LED  
DHCP Indication (1) Green LED  
Output Status (2) Green LED  
Input Status (2) Green LED  
Network (1) RJ45 for Ethernet  
Temp./Humidity (1) RJ11 for ENV probe connection  
Identification 1 Digits Seven Segments for Identification  
Meter 3 Digits Seven Segments

### Power Information

Voltage +/- 2% @ 90V~260V  
Active Power +/- 2% @ 50W~5000W  
Apparent Power +/- 2% @ 50VA~5000VA  
Frequency +/- 2% @ 45~65Hz  
Power Factor +/- 0.02 @ 0.5~1.0  
kWh Range: 0.001kWh ~ 99999.999kWh  
Precision: +/-2% @ 50W~5000W, kh=1.0  
Current Range: 0A ~ 32 A  
Resolution: 0.1A  
Precision: +/-2%/+/-0.1AMP

### Operation

Nominal Voltage 200V ~240V  
On-Line Voltage 180V~ 262V  
Frequency 50/60Hz  
Max. Output Current 32 Amp  
Transfer Time 8~16ms  
Operation Temp. 0 ~ 40 Celsius degree  
Humidity 0% ~ 90%  
Size 260 x 432 x 44.45 mm  
Net Weight 5 kg

### Regulatory Approvals

CE, EN 55022 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3  
FCC Part 15 Class A, ICES-003

