

M O O N R A K E R



Type 100B - 100B/S - 100W

High power capability marine HF whip antenna for professional use and GMDSS fit on ocean-going vessels

The type 100B - 100B/S -100W is a 10 metre (32.8 ft) heavy duty free standing whip antenna with a power capability of 1.2 kW PEP in the frequency range 1.6-30 MHz, designed to provide efficient and reliable communications in the professional services.

The antenna is available either side mounted (100W) or base mounted with base feed (100B) or side feed (100B/S) and is able to withstand wind speeds of 200 km/h (125 mph) without permanent deformation.

Construction is of heavy gauge marine grade aluminium alloy tubing, which provides a large low loss surface area for maximum radiating efficiency. The radiator and base flange are finished with a high durability epoxy based coating, highly resistant to chemical attack, abrasion and the effects of ozone and ultra-violet radiation. The base mount is fabricated aluminium alloy with industry standard 165 mm (6.5 in) O/D flange with eight mounting holes, drilled on 140 mm (5.5 in) centres. Base insulator is ribbed high strength low loss polypropylene. Side mounting is via two ribbed low loss polypropylene insulators. Connection is via a base feedthrough insulator (B) or to a stainless steel side terminal above the base insulator (B/S) or bottom side mount (W).


For ease of transport, the antenna breaks down into three sections which slip together and fasten with stainless steel locking screws. These joints are sealed using a special jointing kit and covered with flexible boots.

A Tilting Mount which may be operated either by hand lowering or by an optional winding handle screw assisted mechanism is available permitting the antenna to be lowered and raised at will when obstructions are encountered and to facilitate maintenance. Mount construction is of hot dip galvanised coated steel with stainless and bronze fittings.

Specifications

Colour	Standard is Black
HF Marine Band	1.6-30 MHz
Length	10.0 metres (32.8 ft)
Pattern	Omnidirectional
Polarisation	Vertical
Frequency Range	Unloaded 1.6-30 MHz with suitable ATU
Wind Loading	72 kg at 200 km/h (158 lbs at 125 mph) Antenna survival : 200 km/h (125 mph), 55m/sec
Tip Deflection	5.56 m at 200 km/h (18.2 ft at 125 mph), 55m/sec
Temperature Rating	-30 to +55° C
Power Capability	Unloaded 1.2 kW PEP
Base Mounting	Industry standard 165 mm (6.5 in) diameter flange with 8 x 13.5 mm (½ in) holes drilled on a 140 mm (5.5 in) diameter
Side Mounting	Two 5/8 in Whitworth bolts into two 110 mm (4.3 in) diameter side mounting insulators, spaced a minimum of 1 m (3.3 ft) apart.
Connection	Side feed via 1/4 in Whitworth s/s stud and lock nuts; base feed below through deckmount via 3/8 in Whit S/S stud and lock nuts
Packed Weight	100B - 33kg (72.6 lbs), 100B/S - 30kg (66.1 lbs), 100W - 21kg (46.2 lbs)

Specifications subject to change – Issued 07/13



Moonraker Australia Pty. Ltd. ABN 70 162 868 475

Tasmanian Technopark, Dowsing Point, Tasmania, Australia 7010

Website: www.moonraker.com.au Tel: 61 (0)3 6273 1533 Fax: 61 (0)3 6273 1749 Email: radiocom@moonraker.com.au

